



دهانات جدة
Jeddah Paints
Since 1983

JP Interior Emulsion 01-100

Product Data Sheet

Product Description: JP Interior is an economical emulsion based styrene acrylic with good coverage and smooth matt finish.

Area of Use: For application on interior concrete, plastered and precast surfaces. Ideal for interior walls and ceilings.

PHYSICAL CONSTANTS

Colour	As per standard color card
Appearance	Matt
Solid Volume	55%
Theoretical Coverage	18.3 M ² per liter @ 30 micron DFT
Density	1.5 Kg/liter
Touch dry	2 to 3 hours
Full Cure	10 hours
VOC	5 g/l

APPLICATION DETAILS

Application method	Spray, brush , roller
Thinner	Fresh water
Thinner %	5% airless, 15% air spray, 10% roller
Airless nozzle orifice	.013"-.015"
Airless nozzle pressure	1500 psi
Recommended DFT	30 to 50 microns
Corresponding WFT	55 to 90 microns
Pot life	NA

Note: The paint shall be thoroughly mixed prior to application. Practical spreading rate/consumption will vary and is influenced by the porosity and nature of the substrate, micro-environment, application method and workmanship.

Application Conditions: Application temperature above 5°C and humidity below 85%. Adequate ventilation to be provided during application and drying. Do not apply in severe weather conditions.

Surface Preparation and Application: The concrete should be fully cured. The substrate should be dry, clean, free from dust or dirt and any other contamination.

Application Procedure: Can easily be applied by roller providing a smooth finish. Apply the emulsion evenly using a roller, Ensure thorough coverage without puddles or missed spots.

The emulsion can be spray applied with airless sprayer. Use fresh water 5% maximum when applying by airless spray, 15% thinning with fresh water for air spray and 10% when applied by roller. Two coats of the topcoat may be necessary to obtain full hiding power.

Preceding Coats : JP Interior Primer Sealer / JP Interior putty .

Subsequent Coats: Can be topcoated by itself .

Storage: Follow local legislation for storage. Avoid storage in direct sunlight preferably covered area with maximum temperature of 40°C and not below 5°C, protect from rain.

Shelf Life: 2 years when stored in shaded spaces.

Safety : Observe all safety labels on packaging and paint containers during application. Follow Material Safety Data Sheets and all local or national safety regulations. Application should be done only in well ventilated areas. Take precautions with contact with skin, eyes, inhalation. Take precautions against possible risks of fire or explosions and protect the environment. For professional use only.