



دهانات جدة
Jeddah Paints
Since 1983

JP Rollato Texture -06-100

Product Data Sheet

Product Description: JP Rollato is an styrene Acrylic in aqueous emulsion, quartz powders, sands, organic and inorganic pigments with outstanding characteristics being resistance to UV and suitable for surfaces that requires alkaline resistance and excellent flexibility to bridge minor cracks.

Area of Use: It is recommended as a decorative finish coat on block walls, plastered surfaces, bricks and concrete surfaces to create a texture pattern as an external decorative finish. The texture can be fine, medium or coarse depending on the aggregate size.

PHYSICAL CONSTANTS	
Colour	White, Color limited can be tinted
Appearance	Fine Texture
Solid Volume	80%
Theoretical Coverage	1 Kg / 1 Square meter
Density	1.79 Kg/liter
Touch dry	2-3 hours
Full Cure	24 hours
VOC	5 gm/l

APPLICATION DETAILS	
Application method	Spray, sponge roller
Thinner	None, Clean tool with fresh water
Thinner %	Not recommended to thin
Airless nozzle orifice	N.A.
Airless nozzle pressure	N.A.
Recommended DFT	0.2 mm
Corresponding WFT	0.3mm
Use life	12 hours

Note: The texture shall be thoroughly mixed prior to application. Practical spreading rate/consumption will vary and is influenced by the porosity and nature of the substrate, micro-environment, application method and workmanship.

Application Conditions: Application temperature above 5°C and humidity below 85%. Adequate ventilation to be provided during application and drying. Do not apply in severe weather conditions.

Surface Preparation: The concrete should be fully cured. The substrate should be dry, clean, free from dust or dirt and any other contamination.

Application Procedure: Apply manually using sponge roller or by using hopper gun or spray machine as a one coat of a thickness of 0.2 mm to 0.3 mm.

Preceding Coats: JP primer and JP Putty, as per the specification.

Subsequent Coats: JP emulsion if required to change color

Storage: Follow local legislation for storage. Avoid storage in direct sunlight preferably covered area with maximum temperature of 40°C and not below 5°C, protect from rain.

Shelf Life: 2 years when stored in shaded spaces.

Safety: Observe all safety labels on packaging and paint containers during application. Follow Material Safety Data Sheets and all local or national safety regulations. Application should be done only in well ventilated areas. Take precautions with contact with skin, eyes, inhalation. Take precautions against possible risks of fire or explosions and protect the environment. For professional use only.