



دهانات جدة
Jeddah Paints
Since 1983

JP Wood Glue White 05-200

Product Data Sheet

Product Description: JP High Density Glue Paste ready to use and made of homo polymer resin in aqueous dispersion with various additives which give this product the outstanding qualities of good and easy workability, viscosity, necessary time for working and strong final grip for internal fixing of tiles.

Area of Use: Recommended for internal laying of ceramic walls and floor tiles onto many different surfaces such as Gypsum plasters or cement plasters.

PHYSICAL CONSTANTS	
Colour	white
Appearance	Viscous fluid
Solid Volume	60%
Theoretical Coverage	1 ltr for 8-10 m ²
Density	1.1 w/L
Touch dry	2-3 hours
Full Cure	24 hours
VOC	5g/l

APPLICATION DETAILS	
Application method	Brush -roller
Thinner	Clean water
Thinner %	Do not use thinner
Airless nozzle orifice	NA
Airless nozzle pressure	NA
Recommended DFT	75µm
Corresponding WFT	100 µm
Use life	12 hours

Note: The glue shall be thoroughly mixed prior to application. Practical spreading rate/consumption will vary and is influenced by the porosity and nature of the substrate, micro-environment, application method and workmanship.

Application Conditions: Application temperature above 5°C and humidity below 85%. Adequate ventilation to be provided during application and drying. Do not apply in severe weather conditions.

Surface Preparation and Application: Surface to be trimmed and flat, remove and clean all traces of oil, grease, wax, form-oil. Ensure all parts are securely abchored to the background. Uniformly spread the glue using a notched trowel. Place the tiles or panels and apply pressure to ensure good contact within 15 minutes of applying the glue.

Preceding Coats : None.

Subsequent Coats: None

Storage: Follow local legislation for storage. Avoid storage in direct sunlight preferably covered area with maximum temperature of 40°C and not below 5°C, protect from rain.

Shelf Life: 2 years when stored in shaded spaces.

Safety : Observe all safety labels on packaging and paint containers during application. Follow Material Safety Data Sheets and all local or national safety regulations. Application should be done only in well ventilated areas. Take precautions with contact with skin, eyes, inhalation. Take precautions against possible risks of fire or explosions and protect the environment. For professional use only.